

SAFETY DATA SHEET

Date Prepared : 02/08/2018
 MSDS No : P9100 & P9300
 Date Revised : 02/08/2018
 Revision No : 1

GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

MANUFACTURER

GLUE 360 INC
 PO BOX 809
 CEDAR CREEK, TX 78612
 Product Stewardship: (833) 360-3606

24 HR. EMERGENCY TELEPHONE NUMBERS

INFOTRAC (US and Canada): 1-800-535-5053
 INFOTRAC (International): 1-352-323-3500

COMMENTS: Safety Data Sheet (SDS) for all P9100 and P9300 series products Exceptions: P9100, P9164, P9165 and P9177

GLUE 360 is a registered trademark of GLUE 360 INC

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Oral), Category 4
 Skin Sensitization, Category 1
 Skin Irritation, Category 2
 Eye Irritation, Category 2B
 Target Organ Toxicity (Single exposure), Category 3

Environmental:

Acute Hazards to the Aquatic Environment, Category 3
 Chronic Hazards to the Aquatic Environment, Category 3

Physical:

Flammable Liquids,

Category 2 GHS LABEL



Flame



Exclamation mark



Exclamation mark

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H226: Flammable liquid and vapour.
 H302: Harmful if swallowed.
 H315: Causes skin irritation.
 H317: May cause an allergic skin reaction.
 H320: Causes eye irritation.
 H335: May cause respiratory irritation.
 H402: Harmful to aquatic life.
 H412: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

Date Prepared : 02/08/2018
 MSDS No : P9100 & P9300
 Date Revised : 02/08/2018
 Revision No : 1

GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

H320: Causes eye irritation.
 H315: Causes skin irritation.
 7708NAHS: Causes respiratory tract irritation.

PRECAUTIONARY STATEMENT(S)

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233: Keep container tightly closed.
 P240: Ground and bond container and receiving equipment.
 P241: Use explosion-proof [electrical/ventilating/lighting/...] equipment.
 P242: Use non-sparking tools.
 P243: Take action to prevent static discharges. P260: Do not breathe dust/fume/gas/mist/vapours/spray.
 P264: Wash thoroughly after handling.
 P270: Do not eat, drink or smoke when using this product.
 P271: Use only outdoors or in a well-ventilated area.
 P272: Contaminated work clothing should not be allowed out of the workplace.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312: Call a POISON CENTER/doctor/...if you feel unwell.
 P321: Specific treatment (see Section 4).
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
 P362: Take off contaminated clothing.
 P370+P378: In case of fire: Use ... to extinguish.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed. P403+P235: Store in a well-ventilated place. Keep cool. P405: Store locked up.

Disposal:

P501: Dispose of contents/container to ...

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: WARNING! FLAMMABLE LIQUID AND VAPOR. Harmful, Skin Sensitizer. Irritant.

POTENTIAL HEALTH EFFECTS

EYES: Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury.

SKIN: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.

INGESTION: Can cause irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.

INHALATION: Respiratory tract irritant. High concentrations may cause dizziness, headache, and anesthetic effects. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.

CARCINOGENICITY: IARC has classified both MMA and benzoyl peroxide as Class 3 agents.

SAFETY DATA SHEET

Date Prepared : 02/08/2018
 MSDS No : P9100 & P9300
 Date Revised : 02/08/2018
 Revision No : 1

GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

MEDICAL CONDITIONS AGGRAVATED: Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

ROUTES OF ENTRY: Eye and Skin Contact, Inhalation and Ingestion

TARGET ORGAN STATEMENT: Eyes. Skin. Respiratory system. Digestive system. Liver. Kidney. Olfactory Function.

IRRITANCY: Eyes, nose, throat, respiratory tract, and skin irritation.

SENSITIZATION: May cause allergic respiratory and skin reaction. Respiratory and skin sensitizer.

3.COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Methyl Methacrylate Monomer (MMA)	45 - 70	80-62-6
Polymethyl Methacrylate	15 - 40	9011-87-4
TSRN 800941-5020P	3 - 10	NA
TSRN 800941-5016P	1 - 5	NA
Benzoyl Peroxide	3 - 10	94-36-0
Diisobutyl Phthalate	25 - 50	84-69-5
Texanol Benzyl Phthalate	25 - 50	16883-83-3
TSRN 800941-5006P	7 - 13	NA

COMMENTS: Note: MMA, Polymethyl Methacrylate, TSRN 800941-5016P and TSRN 800941-5020P are contained in the Adhesive (10) Benzoyl Peroxide, Diisobutyl Phthalate, Texanol Benzyl Phthalate and TSRN 800941-5006P are contained in the Activator (1)

The wt % is based on each formula, not the blended product.

4.FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash or dispose of clothing before reuse.

INGESTION: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Can cause stinging, watering, redness, and swelling.

SKIN: May cause skin irritation; itching, redness, rashes, hives, burning and swelling.

INGESTION: Ingestion of this material can cause mouth, throat and gastrointestinal tract irritation and abdominal pains.

SAFETY DATA SHEET

Date Prepared : 02/08/2018
MSDS No : P9100 & P9300
Date Revised : 02/08/2018
Revision No : 1

GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

INHALATION: Respiratory tract irritation. High concentration may cause dizziness, headache, and anesthetic effects.

ACUTE EFFECTS: Overexposure can cause headaches, dizziness, nausea and vomiting. Irritant.

CHRONIC EFFECTS: Prolonged skin contact may lead to burning associated with severe reddening, swelling and possible tissue destruction.

ADDITIONAL INFORMATION: Due to possible aspiration into the lungs, **DO NOT** induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Class IB

GENERAL HAZARD: Flammable liquid and vapor.

EXTINGUISHING MEDIA: Use carbon dioxide (CO₂) or dry chemical when fighting fires involving this material. **OTHER CONSIDERATIONS:** Water may cause frothing.

EXPLOSION HAZARDS: Sealed containers at elevated temperatures may rupture explosively and spread fire due to polymerization.

FIRE FIGHTING PROCEDURES: Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

FIRE FIGHTING EQUIPMENT: As in any fire, wear Self-Contained Breathing Apparatus (SCBA) MSHA/NIOSH approved or equivalent and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof mechanical means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

COMMENTS: Pump or shovel to storage/salvage vessels. Add inhibitor to prevent polymerization.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around

SAFETY DATA SHEET

Date Prepared : 02/08/2018
MSDS No : P9100 & P9300
Date Revised : 02/08/2018
Revision No : 1

GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

chemical vapors and liquid. Wash hands thoroughly after handling. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation).

HANDLING: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and grounding procedures. Do not reuse containers.

STORAGE: Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, direct sunlight, and incompatible materials. Keep container tightly closed when not in use.

SHELF LIFE: 18 months from manufacture date

COMMENTS: Wash thoroughly after handling.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	Type	EXPOSURE LIMITS		
		TWA	ppm	mg/m ³
Methyl Methacrylate Monomer (MMA)	OSHA PEL	TWA	100 ppm [1]	410 mg/m ³ [1]
		STEL	NL ppm [1]	NL mg/m ³ [1]
	ACGIH TLV	TWA	50 ppm	205 mg/m ³
		STEL	100 ppm	410 mg/m ³
Polymethyl Methacrylate	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
TSRN 800941-5020P	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
TSRN 800941-5016P	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
Benzoyl Peroxide	OSHA PEL	TWA	NL [1]	5 mg/m ³ [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	5 mg/m ³ [1]
		STEL	NL [1]	NL [1]

SAFETY DATA SHEET

Date Prepared : 02/08/2018
MSDS No : P9100 & P9300
Date Revised : 02/08/2018
Revision No : 1

GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

Diisobutyl Phthalate	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	0.45 ppm	5 mg/m ³
		STEL	NL [1]	NL [1]
Texanol Benzyl Phthalate	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
TSRN 800941-5006P	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
Footnotes: 1. NL = Not Listed				

ENGINEERING CONTROLS: Provide sufficient explosion proof mechanical (general and/or local exhaust) ventilation to maintain exposure below the occupational exposure limit and exposure concentration. Use only in a well ventilated area. Ground and bond all equipment.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields, goggles or full-face shield as required by 29 CFR 1910.133 - OSHA Eye and Face Protection Standard. A suitable emergency eye wash station and safety shower should be located near the work station.

SKIN: Wear chemical resistant, impervious gloves.

RESPIRATORY: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

WORK HYGIENIC PRACTICES: Use good hygiene practices when handling this material. Wash hands thoroughly after use.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Adhesive - Paste
Activator - Liquid

ODOR: Fragrant - Adhesive
Mild Ester - Activator

SAFETY DATA SHEET

Date Prepared : 02/08/2018
 MSDS No : P9100 & P9300
 Date Revised : 02/08/2018
 Revision No : 1

GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

ODOR THRESHOLD: Not Determined

COLOR: Various

pH: Not Determined

PERCENT VOLATILE: 3.9

Notes: by weight

FLASHPOINT AND METHOD: 10°C (50°F) TAG CC

Notes: Fine mists explosive below flash point.

FLAMMABLE LIMITS: 1.7 to 12.5

AUTOIGNITION TEMPERATURE: 421°C (790°F)

VAPOR PRESSURE: Adhesive - 28 mmHg

Activator - < 0.5 mmHg

VAPOR DENSITY: 3.5

Notes: Activator - Not Determined

BOILING POINT: 100.5°C (213°F)

Notes: Activator BP - > 550 oF (287.7 oC)

FREEZING POINT: Not Determined

MELTING POINT: -47.7°C (-54.0°F)

Notes: Activator - Not Determined **POUR**

POINT: Not Determined **SOLUBILITY IN**

WATER: Not Determined

PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Determined

EVAPORATION RATE: < 3

Notes: Activator: < 1 (butyl acetate=1)

DENSITY: 7.753 - 8.754

Notes: Activator - Not Determined

PARTICLE SIZE: Not Determined

SPECIFIC GRAVITY: 0.93 to 1.05

Notes: Activator - Not Determined

VISCOSITY: Not Determined

MOLECULAR WEIGHT: Mixture

(VOC): 33.6 gr/L EPA Method 24 VOC

Notes: Activator: Not Determined

OXIDIZING PROPERTIES: Not Determined

10. STABILITY AND REACTIVITY

REACTIVITY: No

HAZARDOUS POLYMERIZATION: Polymerization may occur under certain conditions.

STABILITY: Unstable.

CONDITIONS TO AVOID: Adhesive - Extreme heat, sparks, and open flame. Incompatible materials, oxidizers

SAFETY DATA SHEET

Date Prepared : 02/08/2018
 MSDS No : P9100 & P9300
 Date Revised : 02/08/2018
 Revision No : 1

GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

and oxidizing conditions. Oxygen-free atmospheres or inert gas blanketing. Freezing conditions. Material can soften paint and rubber.

Activator - Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Contamination, direct sunlight, friction and prolonged storage above 100 oF (38 oC).

INCOMPATIBLE MATERIALS: Oxidizing agents, strong acids and strong alkalis.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Methyl Methacrylate Monomer (MMA)	7872 mg/kg (rats)	> 5 g/kg (rabbits)	78000 mg/cub m (4-hr dose - rat)
Polymethyl Methacrylate	No data	No data	No data
Benzoyl Peroxide	6400 mg/kg (rats)	No data	2 mg/L (96-hr dose - guppy)
Diisobutyl Phthalate	10400 to 15000 mg/kg (rats)	10400 mg/kg (guinea pig)	No data
Texanol Benzyl Phthalate	No data	> 10000 mg/kg (rabbits)	No data
TSRN 800941-5006P	No data	No data	No data

CARCINOGENICITY

Chemical Name	IARC Status
Methyl Methacrylate Monomer (MMA)	3
Benzoyl Peroxide	3

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This product contains components that may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

ECOTOXICOLOGICAL INFORMATION: Contains components that are potentially toxic to freshwater and saltwater ecosystems.

BIOACCUMULATION/ACCUMULATION: Contains components with the potential to bio-accumulate.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

GENERAL COMMENTS: Adhesive

DANGER! Rags, steel wool, and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled metal container.

SAFETY DATA SHEET

Date Prepared : 02/08/2018
MSDS No : P9100 & P9300
Date Revised : 02/08/2018
Revision No : 1

GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Adhesives

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: 1133

PACKING GROUP: II

NAERG: 128

OTHER SHIPPING INFORMATION: contains (Methyl Methacrylate Monomer, Benzoyl Peroxide)

ORM-D Small Quantity Exemption

AIR (ICAO/IATA)

SHIPPING NAME: Adhesives

UN/NA NUMBER: 1133

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: II

VESSEL (IMO/IMDG)

SHIPPING NAME: Adhesives

UN/NA NUMBER: 1133

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: II

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



**Flammable
Liquid**

** for containers > 1.3 gallons (4.9 Liters) **

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: Yes PRESSURE GENERATING: No REACTIVITY: Yes ACUTE: Yes CHRONIC: Yes EPCRA

SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt. %	CAS
Methyl Methacrylate Monomer (MMA)	45 - 70	80-62-6
Benzoyl Peroxide	3 - 10	94-36-0

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

SAFETY DATA SHEET

Date Prepared : 02/08/2018
MSDS No : P9100 & P9300
Date Revised : 02/08/2018
Revision No : 1

GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

Chemical Name	Wt.%	CERCLA RQ
Methyl Methacrylate Monomer (MMA)	45 - 70	1,000

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Methyl Methacrylate Monomer (MMA)	80-62-6
Polymethyl Methacrylate	9011-87-4
Benzoyl Peroxide	94-36-0
Diisobutyl Phthalate	84-69-5
Texanol Benzyl Phthalate	16883-83-3

STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Methyl Methacrylate Monomer (MMA)	Massachusetts Right to Know List Minnesota Right to Know List New Jersey Right to Know List Pennsylvania Right to Know List Rhode Island Right to Know List
Benzoyl Peroxide	California Right to Know List Massachusetts Right to Know List Minnesota Right to Know List New Jersey Right to Know List Pennsylvania Right to Know List Rhode Island Right to Know List

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic



Flammable
Liquid

R36/37/38: Irritating to eyes, respiratory system and skin. R43: May cause sensitization by skin contact.

R11: Highly flammable.

WHMIS CLASS: Adhesive - WHMIS Hazard Class: B2, D2B
Activator - WHMIS Hazard Class: D2B

16. OTHER INFORMATION

Date Revised: 02/08/2018

INFORMATION CONTACT: (833) 360-3606

SAFETY DATA SHEET

Date Prepared : 02/08/2018
 MSDS No : P9100 & P9300
 Date Revised : 02/08/2018
 Revision No : 1


GLUE 360 2-Component Solid Surfacing Adhesive (10:1 Ratio) - All Colors

REVISION SUMMARY: This MSDS replaces the 01/09/2015 MSDS. Revised: Section 1: Date Issued. Section 14: AIR (ICAO/IATA) (PRIMARY HAZARD CLASS/DIVISION, PACKING GROUP, UN/NA NUMBER), VESSEL (IMO/IMDG) (PRIMARY HAZARD CLASS/DIVISION, PACKING GROUP, UN/NA NUMBER).

HMIS RATING

HEALTH _____ *	<u>2</u>
FLAMMABILITY _____	<u>3</u>
PHYSICAL HAZARD _____	<u>2</u>
PERSONAL PROTECTION _____	<u>B</u>

NFPA CODES



GENERAL STATEMENTS: Keep out of reach of children

MANUFACTURER DISCLAIMER: This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of GLUE 360 INC. The data on this sheet relates only to the specific material designated herein. GLUE 360 INC assumes no legal responsibility for use or reliance upon these data.